

钛白粉TiO2 TITANIUM DIOXIDE TIO2

INTRODUCTION OF PRODUCTS


Characteristics: R-2195 is rutile titanium dioxide with inorganic and organic surface treatment, which has high whiteness, high hiding power, good tinting strength, good weather resistance and good dispersibility.

Applications: R-2195 is general purpose grade which is widely used in coating, ink, profile, masterbatch, paper, etc.


SPECIFICATION

| Tio ₂ content | ≥93% |
|--------------------------|---------|
| Rutile content | ≥97% |
| Inorganic treatment | Si. Al |
| Organic treatment | YES |
| Particle size (D50) | 0.26 |
| Specific gravity | 4.0 |
| Apparent density | 0.66 |
| Oil absorption | ≤21 |
| CIEL* | ≥94.5 |
| рН | 6.0-9.0 |
| | |

INTRODUCTION OF PERFORMANCE



*The typical particle size distribution



*The contrast ratio of R-2195 in Acrylic latex

B、C、D are import products .E、F、G are famous domestic products.

Hiding power in acrylic latex paint is expressed by contrast ratio, which is tested by BGD-581.

Dawn R-2195 is a general-purpose product. After the inorganic surface treatment of silicon and aluminum, the weatherability of rutile TiO₂ has been significantly improved. In addition, due to the whole production process of slag titanium, R-2195 possesses superior tinting strength and hiding power to other competing products at home.

GRADING STANDARD

ISO591-1: 2000(E) R2

ASTMD476-00 Ш

SAFETY PRECAUTIONS AND FIRST AID

Titanium dioxide is classified as a nuisance dust.

- · As a matter of good industrial hygiene, gloves and safety glasses with side shields or better eye protection should be worn when handling
- If large amounts of TiO, are inhaled, remove victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
- In case of eye contact, immediately flush with water for at least 15 min. Call a physician. In case of skin contact, the compound is not likely to be hazardous, but cleaning the skin after use is advised.

PACKING

- 25KG PLASTIC AND PAPER BAG
- 500KG AND 1000KG TON BAG

SHANDONG DAWN TITANIUM INDUSTRY CO.,LTD.

TEL.:+86-535-8861111 Fax.:+86-535-8869877 Add.:Longkou New Energy and New Material Industrial Park,Longkou Economic Development Zone, Longkou City, Shandong Province, China E-mail: dawntio2@chinadawn.cn Web: www.dawnty.com